

GRAPHITE

Code : G804



- Graphite in engineering testing laboratories is used as a lubricant, conducting material, or for preparing composite materials. It is commonly utilized in high-temperature applications, such as in the production of electrodes, and in tests involving materials like lubricants, electrical conductivity, or wear resistance.

ORDERING INFORMATION

Item	Code
TRICHLOROETHYLENE	G801X00XH
METHYLENE BLUE POWDER - 100 g	G802X00XH
SULPHUR	G803X00XH
GRAPHITE	G804X00XH
SODIUM SULFATE	G805X00XH

MAGNESIUM SULFATE	G806X00XH
-------------------	-----------

BARIUM CHLORIDE	G807X00XH
-----------------	-----------

CALCIUM CHLORIDE	G808X00XH
------------------	-----------

SODIUM HYDROXIDE	G809X00XH
------------------	-----------

FORMALDEHYDE (Stock Solution)	G810X00XH
-------------------------------	-----------

SODIUM HEXAMETAPHOSPHATE	G811X00XH
--------------------------	-----------

SILICA GEL	G812X00XH
------------	-----------

PARAFIN WAX	G813X00XH
-------------	-----------

KAOLINITE	G814X00XH
-----------	-----------

QUANTAB CHLORIDE TITRATOR 1175 TYPE	G815X00XH
-------------------------------------	-----------

QUANTAB CHLORIDE TITRATOR 1176 TYPE	G816X00XH
-------------------------------------	-----------